



“Praktikus 750“ at a glance

Area (W x D)	100 x 200 cm
Weight	from 29 kg
Usable area	2 m ²
Stacking height	9 cm
Traffic load	up to 750 kg/m ² at 1.66 m up to 500 kg/m ² at 1.80 m



Scan the QR code now and watch the installation video


You can find a variety of matching floor coverings on p. 44/45

The all-rounder among the platforms


The Praktikus 750 stage element impresses with its easy handling and high stability. It is used worldwide for indoor and outdoor events. Several elements can be connected to form a large area thanks to an assembly groove. Special designs in various shapes, sizes and heights are possible, including curves or mobile round stages. The Praktikus 750 offers a large selection of coverings and also has logistical advantages with a stacking height of 9 cm.

In accordance with DIN 15921 for actors and DIN EN 13814 for audiences.


- From 29 kg panel weight (with platform floor)
- TÜV-tested up to 750 kg/m² (DIN 15921)
- Flexibility in shape, format and color
- Safety railing 100 kg/m (DIN 15921)
- Compatible with Justo scaffolding technology
- Static proof according to DIN EN 13814




Plug-in feet page 22



Coverings page 44



Accessories page 46



Stairs/railings from page 52

PRAKTIKUS 750



Rectangle

	Art. -No.
100 x 200 cm	11000
100 x 150 cm	11330s
100 x 100 cm	11320
50 x 200 cm	11330
50 x 150 cm	11320s
60,70,80,90 x 100 cm	S
50 x 100 cm	11310
60,70,80,90 x 200 cm	S
122 x 244 cm	11100
100 x 300 cm	11200



Triangle

100 x 100 x 141 cm	11410s
100 x 200 x 223.6 cm	11430s
100 x 51.8 x 100 cm	11410s



Trapezoid

100 x 100 x 100 x 200 cm	11530s
51.8 x 100 x 103.5 x 100 cm	11520s
103.5 x 100 x 155.3 x 100 cm	11530s

S = special shape - available on request

The Praktikus 750 stage elements can be set up quickly and flexibly. With the appropriate accessories it can be used as a grandstand with chairs and TÜV-approved Mott safety railings in any RAL color.

Optimal use of available space



No two stages are the same and every event has different requirements in terms of size, shape and load. The Praktikus plug-in foot stage offers almost any desired shape. For choir events, triangular and trapezoidal elements can be inserted between the standard elements to create a more compact look.



The internal corner brackets significantly increase the stability of the platform frame. They securely fix the plug-in feet and guarantee a stable stand for the platform elements.



Optional quick release for convenience and safety: simply pull up the lever to release, fold down to lock with double pressure. This makes assembly easier.



Simply slide the supplied X-connectors into the assembly groove to firmly connect the platform elements and create a perfectly level surface. Quick dismantling possible.



Additional quick connectors in the edge area stabilize the scenery surface. Use the practical plug-in foot clamps for steps and gradations (see p. 24).

