



No more dragging - the fixed scissor platform

The permanently installed Top 05 scissor platform is mechanically height-adjustable from 20 to 80 cm from the top edge of the hall floor. In just a few minutes, it can be transformed into an event stage without elements having to be carried. When not in use, it is lowered into the pit floor and serves as a sturdy floor. The distance between the elements is only 4 mm. With the help of the lifting aid, a pulling force of 9 kg per person is sufficient to move the platform from the "0 position" to the desired height. It is easy to operate from above using a release key.

"Top 05" at a glance

Area (W x D)	100 x 200 cm
Weight	from approx. 104 kg
Usable area	2 m ²
Pit depth	from 16 cm
Traffic load	750 kg/m ²
Height grid	20 cm up to 80 cm (Grid width 20 cm)



Variety of suitable floor coverings can be found on p. 44/45



Optionally available: If there is no pit floor available and the platforms stand on a substructure, a running surface must be installed for the lifting aid.

Important: The edging may only be installed after the platform has been assembled.



Additional support brackets ensure a load-bearing capacity of 750 kg/m² at a platform height of 40 cm.



The castors serve as a lifting aid and facilitate the lifting of the stage from the ground level "0-position" up to a height of 20 cm.



The lifting aid is activated by lifting the platform element with the unlocking key. This ensures easy assembly with little effort.



All assembly and disassembly steps are carried out simply from above using the practical unlocking key.

